

864 Text Message

Functional Group=TX

This X12 Transaction Set contains the format and establishes the data content of the Text Message Transaction Set (864) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide users with a capability to electronically move messages, contracts, explanations, and other one-time communications. It is the intent of this transaction set to provide electronic communication (messages) for people, not for computer processing. The use of the transaction set to transmit quasi or unique transaction set standards is discouraged. The use of the Text Message transaction set demands of the sender certain detailed information about the recipient. The transaction set's purpose is to provide communication to the recipient in some human-readable form. The recipient's network will dictate what capabilities are available for delivery of the information. It is the responsibility of the sender to obtain this information and include it in the transmission.

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	ISA	Interchange Control Header	M	1			Must use
	GS	Functional Group Header	M	1			Must use

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
0100	ST	Transaction Set Header	M	1			Must use
0200	BMG	Beginning Segment For Text Message	M	1			Must use

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
LOOP ID - MIT					>1		
0100	MIT	Message Identification	M	1			Must use
0800	MSG	Message Text	M	>1			Must use

Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
0100	SE	Transaction Set Trailer	M	1			Must use

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	GE	Functional Group Trailer	M	1			Must use
	IEA	Interchange Control Trailer	M	1			Must use

ISA Interchange Control Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements:
	16

User Option (Usage): Must use

To start and identify an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA01	I01	Authorization Information Qualifier Description: Code identifying the type of information in the Authorization Information All valid standard codes are used.	M	ID	2/2	Must use
ISA02	I02	Authorization Information Description: Information used for additional identification or authorization of the interchange sender or the data in the interchange; the type of information is set by the Authorization Information Qualifier (I01)	M	AN	10/10	Must use
ISA03	I03	Security Information Qualifier Description: Code identifying the type of information in the Security Information All valid standard codes are used.	M	ID	2/2	Must use
ISA04	I04	Security Information Description: This is used for identifying the security information about the interchange sender or the data in the interchange; the type of information is set by the Security Information Qualifier (I03)	M	AN	10/10	Must use
ISA05	I05	Interchange ID Qualifier Description: Code indicating the system/method of code structure used to designate the sender or receiver ID element being qualified	M	ID	2/2	Must use
		Code Name 14 Duns Plus Suffix				
ISA06	I06	Interchange Sender ID Description: Identification code published by the sender for other parties to use as the receiver ID to route data to them; the sender always codes this value in the sender ID element	M	AN	15/15	Must use
		Code Name 072271711 Canada Production CAP 0722717110 US Production 100				
ISA07	I05	Interchange ID Qualifier Description: Code indicating the system/method of code structure used to designate the sender or receiver ID element being qualified All valid standard codes are used.	M	ID	2/2	Must use
ISA08	I07	Interchange Receiver ID Description: Identification code published by the receiver of the data; When sending, it is used by the sender as their sending ID,	M	AN	15/15	Must use

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
		thus other parties sending to them will use this as a receiving ID to route data to them				
ISA09	I08	Interchange Date Description: Date of the interchange	M	DT	6/6	Must use
ISA10	I09	Interchange Time Description: Time of the interchange	M	TM	4/4	Must use
ISA11	I65	Repetition Separator Description: Type is not applicable; the repetition separator is a delimiter and not a data element; this field provides the delimiter used to separate repeated occurrences of a simple data element or a composite data structure; this value must be different than the data element separator, component element separator, and the segment terminator Code Name : Colon @ At] Bracket ^ Carrot Pipe	M		1/1	Must use
		The Home Depot Requirements: <i>This separator can be any non-alpha-numeric character that is also not used as an element separator, segment terminator or elsewhere in the data. If you need your Repetition Separator added to the list to complete testing, please call Home Depot's Electronic Partnership Development Team at 770-433-8211 x10036, option 2.</i>				
ISA12	I11	Interchange Control Version Number Description: Code specifying the version number of the interchange control segments Code Name 00406 Standards Approved for Publication by ASC X12 Procedures Review Board through October 2002	M	ID	5/5	Must use
ISA13	I12	Interchange Control Number Description: A control number assigned by the interchange sender	M	NO	9/9	Must use
ISA14	I13	Acknowledgment Requested Description: Code indicating sender's request for an interchange acknowledgment All valid standard codes are used.	M	ID	1/1	Must use
ISA15	I14	Interchange Usage Indicator Description: Code indicating whether data enclosed by this interchange envelope is test, production or information All valid standard codes are used.	M	ID	1/1	Must use
ISA16	I15	Component Element Separator Description: Type is not applicable; the component element separator is a delimiter and not a data element; this field provides the delimiter used to separate component data elements within a composite data structure; this value must be different than the data element separator and the segment terminator	M		1/1	Must use

GS Functional Group Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 8

User Option (Usage): Must use

To indicate the beginning of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GS01	479	Functional Identifier Code Description: Code identifying a group of application related transaction sets Code Name TX Text Message (864)	M	ID	2/2	Must use
GS02	142	Application Sender's Code Description: Code identifying party sending transmission; codes agreed to by trading partners Code Name 072271711 US Production 072271711 Canada Production C	M	AN	2/15	Must use
GS03	124	Application Receiver's Code Description: Code identifying party receiving transmission; codes agreed to by trading partners	M	AN	2/15	Must use
GS04	373	Date Description: Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year	M	DT	8/8	Must use
GS05	337	Time Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	M	TM	4/8	Must use
GS06	28	Group Control Number Description: Assigned number originated and maintained by the sender	M	N0	1/9	Must use
GS07	455	Responsible Agency Code Description: Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480 All valid standard codes are used.	M	ID	1/2	Must use
GS08	480	Version / Release / Industry Identifier Code Description: Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally	M	AN	1/12	Must use

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
		assigned by user); if code in DE455 in GS segment is T, then other formats are allowed				
		<u>Code</u> <u>Name</u>				
		004060 Standards Approved for Publication by ASC X12 Procedures Review Board through October 2002				

Semantics:

1. GS04 is the group date.
2. GS05 is the group time.
3. The data interchange control number GS06 in this header must be identical to the same data element in the associated functional group trailer, GE02.

Comments:

1. A functional group of related transaction sets, within the scope of X12 standards, consists of a collection of similar transaction sets enclosed by a functional group header and a functional group trailer.

ST Transaction Set Header

Pos: 0100	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	Transaction Set Identifier Code Description: Code uniquely identifying a Transaction Set	M	ID	3/3	Must use
		Code Name 864 Text Message				
ST02	329	Transaction Set Control Number Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M	AN	4/9	Must use

Semantics:

1. The transaction set identifier (ST01) is used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).
2. The implementation convention reference (ST03) is used by the translation routines of the interchange partners to select the appropriate implementation convention to match the transaction set definition. When used, this implementation convention reference takes precedence over the implementation reference specified in the GS08.

BMG Beginning Segment For Text Message

Pos: 0200	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To indicate the beginning of a Text Message Transaction Set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BMG01	353	Transaction Set Purpose Code Description: Code identifying purpose of transaction set All valid standard codes are used.	M	ID	2/2	Must use
BMG02	352	Description Description: A free-form description to clarify the related data elements and their content	O	AN	1/80	Must use

Comments:

1. BMG02 contains the message subject.

Loop MIT

Pos: 0100	Repeat: >1
	Mandatory
Loop: MIT	Elements:
	N/A

To identify the beginning of a specific message and to allow the identification of a subject for the message

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
0100	MIT	Message Identification	M	1		Must use
0800	MSG	Message Text	M	>1		Must use

MIT Message Identification

Pos: 0100	Max: 1
Detail - Mandatory	
Loop: MIT	Elements: 3

User Option (Usage): Must use

To identify the beginning of a specific message and to allow the identification of a subject for the message

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
MIT01	127	Reference Identification Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	M	AN	1/50	Must use
MIT03	931	Page Width Description: Definition of the maximum number of characters per line that can be expected in the message text	O	NO	1/3	Must use
MIT04	932	Page Length Lines Description: Definition of the maximum number of lines per page that can be expected in the message text	O	NO	1/3	Must use

Semantics:

1. MIT01 contains the message number.
2. MIT02 contains the message subject.

Comments:

1. MIT03 default is 80 characters.
2. MIT04 default is 66 lines.

MSG Message Text

Pos: 0800	Max: >1
Detail - Mandatory	
Loop: MIT	Elements: 2

User Option (Usage): Must use

To provide a free-form format that allows the transmission of text information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
MSG01	933	Free-form Message Text	M	AN	1/264	Must use
		Description: Free-form message text				
MSG02	934	Printer Carriage Control Code	X	ID	2/2	Must use
		Description: A field to be used for the control of the line feed of the receiving printer				
		All valid standard codes are used.				

Syntax:

1. C0302 - If MSG03 is present, then all of MSG02 are required

Semantics:

1. MSG03 is the number of lines to advance before printing.

Comments:

1. MSG02 is not related to the specific characteristics of a printer, but identifies top of page, advance a line, etc.
2. If MSG02 is "AA - Advance the specified number of lines before print" then MSG03 is required.

SE Transaction Set Trailer

Pos: 0100	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	Number of Included Segments Description: Total number of segments included in a transaction set including ST and SE segments	M	NO	1/10	Must use
SE02	329	Transaction Set Control Number Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M	AN	4/9	Must use

Comments:

1. SE is the last segment of each transaction set.

GE Functional Group Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To indicate the end of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GE01	97	Number of Transaction Sets Included Description: Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element	M	NO	1/6	Must use
GE02	28	Group Control Number Description: Assigned number originated and maintained by the sender	M	NO	1/9	Must use

Semantics:

1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

Comments:

1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header.

IEA Interchange Control Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To define the end of an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IEA01	I16	Number of Included Functional Groups Description: A count of the number of functional groups included in an interchange	M	NO	1/5	Must use
IEA02	I12	Interchange Control Number Description: A control number assigned by the interchange sender	M	NO	9/9	Must use

Table of Contents

Text Message	1
Interchange Control Header	2
Functional Group Header	4
Transaction Set Header	6
Beginning Segment For Text Message	7
Loop MIT	8
Message Identification	9
Message Text	10
Transaction Set Trailer	11
Functional Group Trailer	12
Interchange Control Trailer	13