

832 Price/Sales Catalog

Functional Group ID=**SC**

Introduction:

This Draft Standard for Trial Use contains the format and establishes the data contents of the Price/Sales Catalog Transaction Set (832) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide for customary and established business and industry practice relative to furnishing or requesting the price of goods or services in the form of a catalog.

Heading:

<u>Page No.</u>	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Base Status</u>	<u>User Status</u>	<u>Max.Use</u>	<u>Loop Repeat</u>	<u>Notes and Comments</u>
2	010	ST	Transaction Set Header	M	M	1		
3	020	BCT	Beginning Segment for Price/Sales Catalog	M	M	1		

Detail:

<u>Page No.</u>	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Base Status</u>	<u>User Status</u>	<u>Max.Use</u>	<u>Loop Repeat</u>	<u>Notes and Comments</u>
			LOOP ID - LIN				>1	
4	010	LIN	Item Identification	O		1		

Summary:

<u>Page No.</u>	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Base Status</u>	<u>User Status</u>	<u>Max.Use</u>	<u>Loop Repeat</u>	<u>Notes and Comments</u>
5	010	CTT	Transaction Totals	M	M	1		n1
6	020	SE	Transaction Set Trailer	M	M	1		

Transaction Set Notes

1. Number of line items (CTT01) is the accumulation of the number of LIN segments. Hash total (CTT02) is not used in this transaction.

Segment: **ST** Transaction Set Header
Position: 010
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the start of a transaction set and to assign a control number
Comments:
Notes: *EXAMPLE: ST*832*0001~*

Data Element Summary

<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Base Attributes</u>	<u>User Attributes</u>
ST01	143	Transaction Set Identifier Code Code uniquely identifying a Transaction Set 832 Price/Sales Catalog	M ID 3/3	M
ST02	329	Transaction Set Control Number Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M AN 4/9	M

Segment: **BCT** Beginning Segment for Price/Sales Catalog
Position: 020
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the beginning of the Price/Sales Catalog Transaction Set and specify catalog purpose and number information

Comments:

Notes: *EXAMPLE: BCT*RC*UPC*****13~*

Data Element Summary

<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Base</u> <u>Attributes</u>	<u>User</u> <u>Attributes</u>
BCT01	683	Catalog Purpose Code Code indicating purpose of catalog RC Resale Catalog	M ID 2/2	M
BCT02	684	Catalog Number Identifying number for catalog or superseded catalog	O AN 1/15	AN 2/2
<i>UPC - UPC CATALOG</i>				
BCT10	353	Transaction Set Purpose Code Code identifying purpose of transaction set 11 Response 13 Request	O ID 2/2	

MODELLS SPORTING GOODS EDI SPECIFICATIONS

Segment: **LIN** Item Identification
Position: 010
Loop: LIN Optional
Level: Detail
Usage: Optional
Max Use: 1
Purpose: To specify basic item identification data
Comments: 1 See the Data Dictionary for a complete list of IDs.
 2 LIN02 through LIN31 provide for fifteen different product/service IDs for each item. For example:
 Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.
Notes: *EXAMPLE: LIN*000001*VC*365507831~*

Data Element Summary

<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Base Attributes</u>	<u>User Attributes</u>
LIN01	350	Assigned Identification Alphanumeric characters assigned for differentiation within a transaction set	O AN 1/20	AN 1/6
LIN02	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) UP U.P.C. Consumer Package Code (1-5-5-1) VC Vendor's (Seller's) Catalog Number	M ID 2/2	M
LIN03	234	Product/Service ID Identifying number for a product or service	M AN 1/48	M AN 1/30

MODELLS SPORTING GOODS EDI SPECIFICATIONS

Segment: **CTT** Transaction Totals
Position: 010
Loop:
Level: Summary
Usage: Mandatory
Max Use: 1
Purpose: To transmit a hash total for a specific element in the transaction set
Comments: 1 This segment is intended to provide hash totals to validate transaction completeness and correctness.

Data Element Summary

<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Base</u>	<u>User</u>
<u>Des.</u>	<u>Element</u>		<u>Attributes</u>	<u>Attributes</u>
CTT01	354	Number of Line Items	M N0 1/6	M
		Total number of line items in the transaction set		

Segment: **SE** Transaction Set Trailer
Position: 020
Loop:
Level: Summary
Usage: Mandatory
Max Use: 1
Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)
Comments: 1 SE is the last segment of each transaction set.

Data Element Summary

<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Base Attributes</u>	<u>User Attributes</u>
SE01	96	Number of Included Segments Total number of segments included in a transaction set including ST and SE segments	M N0 1/10	M
SE02	329	Transaction Set Control Number Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M AN 4/9	M